

View Online at <https://aerobasegroup.com/nsn/4730-00-402-5647>

Thickness:

Between 0.470 inches and 0.530 inches

Tube Outside Diameter For Which Designed:

Between 1.970 inches and 2.030 inches

Neck Diameter:

Between 2.850 inches and 2.910 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 2.710 inches and 2.730 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 3.190 inches and 3.210 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.500 inches and 0.560 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.410 inches and 0.470 inches

Bolt Hole Quantity:

4

Flange Length:

Between 4.230 inches and 4.290 inches

Flange Width:

Between 3.570 inches and 3.630 inches

Bolt Hole Diameter:

Between 0.376 inches and 0.383 inches

Neck Height:

Between 0.650 inches and 0.710 inches

Flange Section Style:

Plain face, long neck

Face Seating Surface Condition:

Machined

Special Features:

Two 1/4-28 unf-3b mtg holes through flange spaced 3.500 in. C to c along length

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/12, t6 federal specification single material response

Surface Treatment:

Paint

Style Designator:

Rectangular, with bolt holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23300