

View Online at <https://aerobasegroup.com/nsn/4730-00-419-6207>

Body Style:

Relieved

Concentric Hole Depth:

1.812 inches

Concentric Hole Diameter:

0.500 inches

Overall Length:

2.438 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Cotter Pin Hole Diameter:

Between 0.030 inches and 0.040 inches

Width Across Flats:

0.875 inches

First End Thread Length:

0.281 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

0.032 inches

First Diameter From Wrenching Feature:

0.747 inches

Second Diameter From Wrenching Feature:

0.625 inches

Third Diameter From Wrenching Feature:

0.573 inches

Fourth Diameter From Wrenching Feature:

0.660 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.188 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.812 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

1.875 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

1.969 inches

First Radial Fluid Hole Diameter:

0.265 inches

Distance From First Radial Hole Center To End Of Bolt:

1.812 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

2.250 inches

Wrenching Feature Height:

0.188 inches

First End Thread Series Designator:

Unf

First End Thread Size:

0.750 inches

Material:

Aluminum

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-c-5541 spec.