Quick Disconnect Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-420-0046

| Thread Class: | |
|--------------------------------------------------------------------|--|
| 3a all ends | |
| Overall Length: | |
| 2.217 inches | |
| Quick Disconnect Method: | |
| Push-pull all ends | |
| Connection Style: | |
| Flared all ends | |
| Leg Length: | |
| 0.684 inches | |
| Connection Type: | |
| Threaded external tube first fluid end connection | |
| Features Provided: | |
| Self-sealing | |
| Thread Size: | |
| 0.750 inches all ends | |
| Seat Angle: | |
| 37.0 degrees | |
| Outside Diameter Tube Accommodated: | |
| 0.500 inches all ends | |
| Material: | |
| Aluminum alloy body | |
| Material Specification: | |
| Qq-a-225/6, t4 federal specification single material response body | |
| Surface Treatment: | |
| Anodize body | |
| Surface Treatment Specification: | |
| Mil-a-8625 military specification single treatment response body | |
| Style Designator: | |
| Male coupling half | |
| Thread Series Designator: | |
| Unf all ends | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A531t0 | |
| Mil-std (military Standard): | |
| Mil-a-8625 spec. | |