## NSN 4730-00-433-2582

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-433-2582 **Thread Class:** 3a first fluid end connection **Overall Length:** 3.460 inches Second Leg Length: 0.546 inches **Quick Disconnect Method:** Quick lead thread all ends Mounting Flange Shape Style (non-core): Err-090 **Mounting Flange Outside Diameter:** 1.812 inches **Mounting Flange Bolt Hole Quantity: Mounting Flange Bolt Hole Diameter:** 0.201 inches **Mounting Flange Bolt Circle Diameter:** 1.437 inches **Distance From Mounting Flange To Fluid End:** 1.109 inches **Maximum Operating Temp:** 71.1 degrees celsius 1st response **Connection Style:** Flared first fluid end connection Leg Length: 0.546 inches **Connection Type:** Threaded external tube first fluid end connection **Features Provided:** Self-sealing Second End Relationship With First End: **Maximum Operating Pressure And Media For Which Designed:** 3000.0 pounds per square inch hydraulic fluid, petroleum base **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches first fluid end connection **Mounting Flange Location:** First leg

Seat Angle:

37.0 degrees

## NSN 4730-00-433-2582

Fiig: A531s0

Quick Disconnect Coupling Assembly - Page 2 of 2



## Maximum Operating Tempurature And Media For Which Designed: Err-070 **Outside Diameter Tube Accommodated:** 0.250 inches first fluid end connection Material: Aluminum alloy **Surface Treatment:** Anodize Style Designator: Coupling assembly **Thread Series Designator:** Unjf first fluid end connection Shelf Life: N/a **Unit Of Measure:** Demilitarization: No