NSN 4730-00-433-2583

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-433-2583 **Thread Class:** 3a first fluid end connection **Overall Length:** 3.910 inches Second End Style Designator (non-core): Err-090 **Second End Outside Diameter Tube Accommodated:** 0.375 inches **Second End Thread Class:** За **Quick Disconnect Method:** Quick lead thread all ends **Second Fluid End Connection Type:** Threaded external tube Mounting Flange Shape Style (non-core): **Mounting Flange Outside Diameter:** 2.000 inches **Mounting Flange Bolt Hole Quantity: Mounting Flange Bolt Hole Diameter:** 0.201 inches **Mounting Flange Bolt Circle Diameter:** 1.090 inches **Distance From Mounting Flange To Fluid End:** 1.320 inches **Connection Style:** Flared first fluid end connection **Connection Type:** Threaded external tube first fluid end connection **Features Provided:** Self-sealing Second End Relationship With First End: Not identical **Maximum Operating Pressure And Media For Which Designed:** 3000.0 pounds per square inch hydraulic fluid, petroleum base **Thread Size:** 0.562 inches first fluid end connection **Mounting Flange Location:** First leg

Seat Angle:

37.0 degrees

NSN 4730-00-433-2583

Quick Disconnect Coupling Assembly - Page 2 of 2



Second End Seat Angle:
37.0 degrees
Second End Thread Size:
0.562 inches
Second End Thread Series Designator:
Unf
Outside Diameter Tube Accommodated:
0.375 inches first fluid end connection
Material:
Aluminum alloy
Surface Treatment:
Anodize
Style Designator:
Coupling assembly
Thread Series Designator:
Unf first fluid end connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A531s0