

View Online at <https://aerobasegroup.com/nsn/4730-00-433-2585>

**Thread Class:**

3a first fluid end connection

**Overall Length:**

4.930 inches

**Second End Style Designator (non-core):**

Err-090

**Second End Outside Diameter Tube Accommodated:**

0.625 inches

**Second End Thread Class:**

3a

**Quick Disconnect Method:**

Quick lead thread all ends

**Second Fluid End Connection Type:**

Threaded external tube

**Mounting Flange Shape Style (non-core):**

Err-090

**Mounting Flange Outside Diameter:**

2.500 inches

**Mounting Flange Bolt Hole Quantity:**

6

**Mounting Flange Bolt Hole Diameter:**

0.201 inches

**Mounting Flange Bolt Circle Diameter:**

2.130 inches

**Distance From Mounting Flange To Fluid End:**

1.690 inches

**Connection Style:**

Flared first fluid end connection

**Connection Type:**

Threaded external tube second fluid end connection

**Features Provided:**

Self-sealing

**Second End Relationship With First End:**

Not identical

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches second fluid end connection

**Mounting Flange Location:**

First leg

**Seat Angle:**

37.0 degrees

**Second End Seat Angle:**

37.0 degrees

**Second End Thread Size:**

0.875 inches

**Second End Thread Series Designator:**

Unf

**Outside Diameter Tube Accommodated:**

0.625 inches all ends

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Style Designator:**

Coupling assembly

**Thread Series Designator:**

Unf second fluid end connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531s0