

View Online at <https://aerobasegroup.com/nsn/4730-00-438-5036>

**Head Diameter:**

2.000 inches

**Distance From Centerline To Flat:**

Between 0.875 inches and 0.880 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal tube

**Second End Thread Class:**

3b

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

0.096 inches

**End Application:**

Viking s-3a aircraft

**First End Thread Length:**

0.760 inches

**Second End Thread Length:**

Between 0.120 inches and 0.121 inches

**Wrenching Feature Style:**

Round with wrench flats

**Distance From Bolt End To Hole Center:**

2.850 inches

**Min. Tensile Strength (psi):**

200000 pounds per square inch

**Hardness Rating:**

Between 43.0 rockwell c and 46.0 rockwell c

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.750 inches

**Second End Thread Size:**

0.250 inches

**Second End Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0