## NSN 4730-00-438-5036

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-438-5036

Head Diameter:
2.000 inches
Distance From Centerline To Flat:
Between 0.875 inches and 0.880 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded internal tube
Second End Thread Class:
3b
Second End Thread Direction:
Right-hand
Cotter Pin Hole Diameter:
0.096 inches
End Application:
Viking s-3a aircraft
First End Thread Length:
0.760 inches
Second End Thread Length:
Between 0.120 inches and 0.121 inches
Wrenching Feature Style:
Round with wrench flats
Distance From Bolt End To Hole Center:
2.850 inches
Min. Tensile Strength (psi):
200000 pounds per square inch
Hardness Rating:
Between 43.0 rockwell c and 46.0 rockwell c
First End Thread Series Designator:
Unf
First End Thread Size:
0.750 inches
Second End Thread Size:
0.250 inches
Second End Thread Series Designator:
Unf

## NSN 4730-00-438-5036

Fluid Passage Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A121a0