

View Online at <https://aerobasegroup.com/nsn/4730-00-489-2500>

**Thread Class:**

3a all ends

**Maximum Operating Temp:**

-65.0 degrees fahrenheit single response

**End Application:**

05a helicopter, chinook, ch-47

**Connection Style:**

Flareless (tube) all ends

**Leg Length:**

2.000 inches 1st end

**Connection Type:**

Threaded external tube all ends

**Thready Qty Per Inch (tpi):**

12 all ends

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

1.312 inches 1st end bulkhead

**Seat Angle:**

12.0 degrees all ends

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

1.000 inches all ends

**Material:**

Aluminum alloy 2014 or aluminum alloy 7075

**Material Specification:**

Qq-a-367, t6 federal specification 1st material response or qq-a-367, t73 federal specification 2nd material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2.CI 1 Or 2 military specification single treatment response

**Thread Series Designator:**

Unj all ends

**Specification Data:**

96906-ms21926 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-a-8625 spec.