

View Online at https://aerobasegroup.com/nsn/4730-00-491-7745

| Thread Class:   |
|---|
| 3a 1st end  |
| Bolt Hole Quantity:   |
| 4 2nd end   |
| Connection Style:   |
| Flared (tube) 1st end   |
| Width:  |
| 1.440 inches 2nd end  |
| Length:   |
| 1.440 inches 2nd end  |
| Flange Shape:   |
| Rectangular with holes 2nd end                                  |
| Connection Type:  |
| Threaded external tube 1st end                                  |
| Thready Qty Per Inch (tpi):                                     |
| 12 1st end  |
| Thread Size:  |
| 1.062 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Thickness:  |
| 0.620 inches 2nd end  |
| Bolt Hole Diameter:   |
| 0.218 inches 2nd end  |
| Center To Center Distance Between Bolt Holes Along Length:      |
| 0.636 inches 2nd end  |
| Center To Center Distance Between Bolt Holes Along Width:       |
| 0.636 inches 2nd end  |
| Flange Face Design:   |
| Plain 2nd end   |
| Outside Diameter Tube Accommodated:                             |
| 0.750 inches 1st end  |
| Nominallength:  |
| 2.713 inches  |
| Material:   |
| Steel comp 304  |
| Material Specification:   |
| Qq-s-763, cl 304 federal specification single material response |
| Surface Treatment:  |
| Passivate outside   |
| Surface Treatment Specification:                                |
|   |

Mil-s-5002 military specification single treatment response inside



**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A080b0

## Mil-std (military Standard):

Mil-f-14072 spec.