

View Online at <https://aerobasegroup.com/nsn/4730-00-495-3409>

Thread Class:

2a all ends

End Application:

B-1 aircraft support equipment. Lvs power unit mk48 and trailer family. Armament weapons support equipment (awse). Hh-60h search and rescue, uscg hh-60j search and rescue helicopters. M9 armored combat earth mover. P23 fire/crash truck. Shipboard material handling equipment (mhe). 20-ton wheel mtd w/blk tackle crane.

Connection Style:

Flared (tube) 1st end

Leg Length:

1.703 inches 2nd end

Connection Type:

Threaded external tube 1st end

Thread Size:

0.875 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees

Criticality Code Justification:

Feat

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Special Features:

Weapon system essential. Features - supports anthony model mlt 6-2; nsn: 3930-00-327-1575.

Material:

Steel comp 12l14 or steel

Media For Which Designed:

Fluid single response

Surface Treatment:

Zinc

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

1 flared sleeve and 1 locknut and 1 preformed packing and 1 short coupling nut and 1 flat washer

Specification Data:

96906-ms51527 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

10a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0