## NSN 4730-00-506-9758

Fluid Passage Bolt - Page 1 of 2

3.690 inches



View Online at https://aerobasegroup.com/nsn/4730-00-506-9758

Body Style:
Plain
Concentric Hole Depth:
2.012 inches
Concentric Hole Diameter:
Between 0.203 inches and 0.213 inches
Overall Length:
4.002 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Cotter Pin Hole Diameter:
0.141 inches
End Application:
Mvf joint stars program
Width Across Flats:
0.938 inches
First End Thread Length:
0.500 inches
Wrenching Feature Style:
Hexagon
Distance From Bolt End To Hole Center:
0.190 inches
First Diameter From Wrenching Feature:
0.624 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
3.190 inches
First Radial Fluid Hole Diameter:
0.086 inches
Second Radial Fluid Hole Diameter:
0.086 inches
Distance From First Radial Hole Center To End Of Bolt:
3.500 inches
Distance From Second Radial Hole Center To End Of Bolt:
2.020 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:

## NSN 4730-00-506-9758

Fluid Passage Bolt - Page 2 of 2



Wrenching Feature Height:
0.312 inches
Min. Tensile Strength (psi):
180000 pounds per square inch
First End Thread Series Designator:
Unf
First End Thread Size:
0.625 inches
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, class 3 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A121a0