

View Online at <https://aerobasegroup.com/nsn/4730-00-537-2805>

Body Style:

Body wrenching

Concentric Hole Diameter:

Between 0.276 inches and 0.291 inches

Overall Length:

2.125 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

2a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

First End Thread Length:

0.290 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.3834 inches and 0.3850 inches

Second Diameter From Wrenching Feature:

Between 0.5590 inches and 0.5600 inches

Third Diameter From Wrenching Feature:

Between 0.480 inches and 0.485 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 0.140 inches and 0.142 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Between 0.963 inches and 0.973 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

1.083 inches

First Radial Fluid Hole Diameter:

0.250 inches

Distance From First Radial Hole Center To End Of Bolt:

0.859 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.343 inches

First End Thready Qty Per Inch (tpi):

18

First End Thread Series Designator:

Unf

First End Thread Size:

0.5625 inches

Material:

Steel comp 4140 or steel comp 4130 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6758 military specification single material response or mil-s-6049 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0

Mil-std (military Standard):

Mil-s-5626 spec.