

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3188>

Groove Depth:

Between 0.040 inches and 0.050 inches

Groove Width:

Between 0.068 inches and 0.078 inches

Bolt Circle Diameter:

2.125 inches

Flange Diameter:

3.250 inches

Thickness:

0.688 inches

Socket Diameter:

0.540 inches

Bore Diameter:

0.398 inches

Pipe Size For Which Designed:

0.250 inches

Bolt Hole Quantity:

3

End Application:

Hzn borrestal class cv

Bolt Hole Diameter:

0.562 inches

Neck Height:

0.500 inches

Flange Section Style:

Plain face, socket brazing neck

Groove Cross-sectional Shape:

Rectangular

Groove Pitch Diameter:

Between 0.569 inches and 0.599 inches

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

150.0 pounds per square inch steam and 150.0 pounds per square inch water, salt and 250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

Maximum Operating Temperature And Media For Which Designed:

150.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water, salt and 425.0 degrees fahrenheit steam and 250.0 degrees fahrenheit water, salt

Material:

Copper alloy

Material Specification:

Mil-f-20042 military specification single material response

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type and plain, 250lb class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300

Mil-std (military Standard):

Mil-f-20042 spec.