

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3190>

Bolt Circle Diameter:

2.438 inches

Flange Diameter:

Between 3.562 inches and 3.625 inches

Thickness:

Between 0.688 inches and 0.719 inches

Socket Diameter:

Between 0.812 inches and 0.840 inches

Bore Diameter:

0.688 inches

Pipe Size For Which Designed:

0.500 inches

Bolt Hole Quantity:

3

End Application:

Hzn borrestal class cv

Bolt Hole Diameter:

Between 0.531 inches and 0.562 inches

Neck Height:

0.625 inches

Flange Section Style:

Plain face, socket brazing neck

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

150.0 pounds per square inch steam and 150.0 pounds per square inch water, salt and 250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

Maximum Operating Temperature And Media For Which Designed:

150.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water, salt and 425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water, salt

Material:

Copper alloy

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300