

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3190>

**Bolt Circle Diameter:**

2.438 inches

**Flange Diameter:**

Between 3.562 inches and 3.625 inches

**Thickness:**

Between 0.688 inches and 0.719 inches

**Socket Diameter:**

Between 0.812 inches and 0.840 inches

**Bore Diameter:**

0.688 inches

**Pipe Size For Which Designed:**

0.500 inches

**Bolt Hole Quantity:**

3

**End Application:**

Hzn borrestal class cv

**Bolt Hole Diameter:**

Between 0.531 inches and 0.562 inches

**Neck Height:**

0.625 inches

**Flange Section Style:**

Plain face, socket brazing neck

**Face Seating Surface Condition:**

Machined

**Maximum Operating Pressure And Media For Which Designed:**

150.0 pounds per square inch steam and 150.0 pounds per square inch water, salt and 250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

**Maximum Operating Temperature And Media For Which Designed:**

150.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water, salt and 425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water, salt

**Material:**

Copper alloy

**Style Designator:**

Round, one bolt hole circle

**Specification Or Standard:**

Pr type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23300