

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3195>

Bolt Circle Diameter:

4.438 inches

Flange Diameter:

Between 5.562 inches and 5.645 inches

Thickness:

Between 0.812 inches and 0.850 inches

Socket Diameter:

2.375 inches

Bore Diameter:

2.250 inches

Pipe Size For Which Designed:

2.000 inches

Tube Outside Diameter For Which Designed:

2.375 inches

Bolt Hole Quantity:

6

End Application:

Hzn borrestal class cv

Bolt Hole Diameter:

Between 0.636 inches and 0.688 inches

Neck Height:

0.938 inches

Flange Section Style:

Plain face, socket brazing neck

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

Maximum Operating Temperature And Media For Which Designed:

425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water, salt

Material:

Copper alloy

Precious Material And Weight:

0.126 silver ounces, troy

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type and plain, 250 lb class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23300

Mil-std (military Standard):

Mil-f-20042 spec.