

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3195>

**Bolt Circle Diameter:**

4.438 inches

**Flange Diameter:**

Between 5.562 inches and 5.645 inches

**Thickness:**

Between 0.812 inches and 0.850 inches

**Socket Diameter:**

2.375 inches

**Bore Diameter:**

2.250 inches

**Pipe Size For Which Designed:**

2.000 inches

**Tube Outside Diameter For Which Designed:**

2.375 inches

**Bolt Hole Quantity:**

6

**End Application:**

Hzn borrestal class cv

**Bolt Hole Diameter:**

Between 0.636 inches and 0.688 inches

**Neck Height:**

0.938 inches

**Flange Section Style:**

Plain face, socket brazing neck

**Face Seating Surface Condition:**

Machined

**Maximum Operating Pressure And Media For Which Designed:**

250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

**Maximum Operating Temperature And Media For Which Designed:**

425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water, salt

**Material:**

Copper alloy

**Precious Material And Weight:**

0.126 silver ounces, troy

**Style Designator:**

Round, one bolt hole circle

**Specification Or Standard:**

Pr type and plain, 250 lb class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23300

**Mil-std (military Standard):**

Mil-f-20042 spec.