

View Online at <https://aerobasegroup.com/nsn/4730-00-541-3199>

Bolt Circle Diameter:

6.562 inches

Flange Diameter:

7.688 inches

Thickness:

1.000 inches

Socket Diameter:

4.500 inches

Pipe Size For Which Designed:

4.000 inches

Tube Outside Diameter For Which Designed:

4.500 inches

Bolt Hole Quantity:

8

End Application:

Hzn borrestal class cv

Bolt Hole Diameter:

0.688 inches

Neck Height:

0.938 inches

Flange Section Style:

Plain face, socket brazing neck

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

150.0 pounds per square inch steam and 150.0 pounds per square inch water, salt and 250.0 pounds per square inch steam and 250.0 pounds per square inch water, salt

Maximum Operating Temperature And Media For Which Designed:

150.0 degrees fahrenheit steam and 150.0 degrees fahrenheit water, salt and 425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water, salt

Material:

Copper alloy

Precious Material And Weight:

0.472 silver ounces, troy

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type and plain, 150 lb class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300

Mil-std (military Standard):

Mil-f-20042 spec.