

View Online at <https://aerobasegroup.com/nsn/4730-00-541-6613>

Body Style:

Plain

Concentric Hole Depth:

1.156 inches

Concentric Hole Diameter:

0.172 inches

Overall Length:

1.375 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

Between 0.684 inches and 0.692 inches

First End Thread Length:

0.438 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.431 inches and 0.435 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.750 inches

First Radial Fluid Hole Diameter:

0.188 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 0.771 inches and 0.791 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.188 inches

Wrenching Feature Height:

0.188 inches

Min. Tensile Strength (psi):

125000 pounds per square inch

First End Thread Series Designator:

Unf

First End Seat Angle:

45.0 degrees

First End Thread Size:

0.438 inches

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 or steel comp 321

Surface Treatment:

Passivate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0