# NSN 4730-00-541-6613

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-541-6613

-	
	Body Style:
	Plain
	Concentric Hole Depth:
	.156 inches
C	Concentric Hole Diameter:
0	0.172 inches
C	Overall Length:
1	.375 inches
F	First End Connection Type:
Т	hreaded external tube
F	First End Style Designator:
F	Flared
F	First End Thread Class:
3	Ba
F	First End Thread Direction:
F	Right-hand
V	Vidth Across Flats:
B	Between 0.684 inches and 0.692 inches
F	First End Thread Length:
0	0.438 inches
۷	Vrenching Feature Style:
F	lexagon
F	First Diameter From Wrenching Feature:
E	Between 0.431 inches and 0.435 inches
L	ength From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0	).750 inches
F	First Radial Fluid Hole Diameter:
0	).188 inches
0	Distance From First Radial Hole Center To End Of Bolt:
E	Between 0.771 inches and 0.791 inches
L	ength From Bearing Surface Of Wrenching Feature To Bolt End:
1	.188 inches
V	Vrenching Feature Height:
0	0.188 inches
N	/in. Tensile Strength (psi):
1	25000 pounds per square inch
F	First End Thread Series Designator:
ι	Jnf
F	First End Seat Angle:
4	5.0 degrees
F	First End Thread Size:
0	0.438 inches

## NSN 4730-00-541-6613

Fluid Passage Bolt - Page 2 of 2



Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 or steel comp 321

#### Surface Treatment:

Passivate

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

#### Fiig:

A121a0