NSN 4730-00-542-5106

Pipe Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-542-5106

| Pipe Size Accommodated: |
|--|
| 1.500 inches all ends |
| Maximum Operating Temp: |
| 425.0 degrees fahrenheit 1st response |
| End Application: |
| Poseidon submarine |
| Connection Style: |
| Socket w/ grove (pipe) all ends |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Maximum Operating Pressure: |
| 400.0 pounds per square inch 2nd response |
| Pipe Wall Thickness Designation For Which Designed: |
| Standard all ends |
| Nominallength: |
| 1.920 inches |
| Special Features: |
| Grooved w/brazing rings packaged separately |
| Material: |
| Copper alloy 903 or copper alloy 922 |
| Material Specification: |
| Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| Style Designator: |
| Plain w/concave sides |
| Furnished Items And Quantity: |
| 2 brazing ring |
| Specification Data: |
| 81349-mil-f-1183h government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A080b0 |
| Mil-std (military Standard): |
| Mil-f-1183 spec. |