NSN 4730-00-542-5146

Pipe Elbow - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-542-5146

1.500 inches all ends Maximum Operating Temp: 425.0 degrees fahrenheit 1st response End Application: Jim knox class if Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unithreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved wibrazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b81 assn standard 2nd material response or astm-b82 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mill-1188h government specification Shelf Life: No Unit Of Measure: — Demilitarization: No Filig:	Pipe Size Accommodated:
Maximum Operating Temp: 425.0 degrees fahrenheit 1st response End Application: Jim knox class ff Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Cq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Brazing ring Specification Data: Brazing ring Specification Date: Brazing ring Specification Date: Brazing ring Unit Of Measure: Unitification: Unit Of Measure: Unitification: Unit Of Measure: Unitification: Unitification	
425.0 degrees fahrenheit 1st response End Application: Um knox class if Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 900.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-F-1183h government specification Sheff Life: Na Unit Of Measure: — Demilitarization: No Flig:	
End Application: Unr knox class if Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Welai For Which Designed: Waler-oil-gas 2nd response Medial For Which Designed: Waler-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: Na Unit Of Measure: — Domilitarization: No Flig:	
Um knox class ff Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.404 inchas all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	
Connection Style: Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-0-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81:349-mil-1-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	
Streamlined w/ one brazing ring (pipe) all ends Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Plipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mill-1183h government specification Shelf Life: N/a Unit Of Measure:	
Leg Length: 1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	
1.840 inches all ends Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved wbrazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	
Connection Type: Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-milf-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Unthreaded internal pipe all ends Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-milf-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Maximum Operating Pressure: 400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved wibrazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
400.0 pounds per square inch 2nd response Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mill-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Flow Angle: 90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure:	
90.0 degrees Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	
Pipe Wall Thickness Designation For Which Designed: Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	-
Standard all ends Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Special Features: Grooved w/brazing rings packaged separately Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Material: Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Copper alloy 903 or copper alloy 922 Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Grooved w/brazing rings packaged separately
Material Specification: Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Copper alloy 903 or copper alloy 922
material response Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Media For Which Designed: Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-c-390 federal specification 1st material response or astm-b61 assn standard 2nd material response or astm-b62 assn standard 3rd
Water-oil-gas 2nd response Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	material response
Furnished Items And Quantity: 2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which Designed:
2 brazing ring Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Water-oil-gas 2nd response
Specification Data: 81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Furnished Items And Quantity:
81349-mil-f-1183h government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2 brazing ring
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-f-1183h government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A080b0	Fiig:
	A080b0