

View Online at <https://aerobasegroup.com/nsn/4730-00-552-3496>

Thread Class:

3b 1st end

Maximum Operating Temp:

204.0 degrees celsius 2nd response

End Application:

Aircraft application

Connection Style:

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

Leg Length:

2.280 inches 2nd end

Connection Type:

Threaded internal tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

12.0 degrees 1st end

Flow Angle:

90.0 degrees

Inside Diameter Hose Accommodated:

0.422 inches 2nd end

Outside Diameter Hose Accommodated:

0.742 inches 2nd end

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Material:

Steel comp 347 or steel comp 304

Material Specification:

Qq-s-763, cond a federal specification single material response

Media For Which Designed:

Hydraulic fluid 2nd response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-83298 military specification single treatment response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-83298 spec.