

View Online at <https://aerobasegroup.com/nsn/4730-00-552-3496>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

204.0 degrees celsius 2nd response

**End Application:**

Aircraft application

**Connection Style:**

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

**Leg Length:**

2.280 inches 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Inside Diameter Hose Accommodated:**

0.422 inches 2nd end

**Outside Diameter Hose Accommodated:**

0.742 inches 2nd end

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Steel comp 347 or steel comp 304

**Material Specification:**

Qq-s-763, cond a federal specification single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-83298 military specification single treatment response

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-83298 spec.