## NSN 4730-00-555-8054

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-555-8054

soay Style:
Plain
Concentric Hole Depth:
.313 inches
Concentric Hole Diameter:
0.297 inches
Overall Length:
.563 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Plain
First End Thread Class:
3a
First End Thread Direction:
Right-hand
Nidth Across Flats:
0.813 inches
First End Thread Length:
0.469 inches
Vrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature:
0.560 inches
ength From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0.875 inches
First Radial Fluid Hole Diameter:
0.250 inches
Distance From First Radial Hole Center To End Of Bolt:
0.875 inches
ength From Bearing Surface Of Wrenching Feature To Bolt End:
.344 inches
Vrenching Feature Height:
0.219 inches
First End Thread Series Designator:
Jnf
First End Thread Size:
0.563 inches
Material:
Steel comp 304l or steel comp 347
Surface Treatment:
Passivate

## NSN 4730-00-555-8054

Fluid Passage Bolt - Page 2 of 2



		<b>a</b> 161 41	
Surtace	I reatment	Specification	•

Mil-s-5002 military specification single treatment response

**Specification Data:** 

88044-an775 government standard and 81343-as4875 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-s-5002 spec.