

View Online at <https://aerobasegroup.com/nsn/4730-00-559-1604>

**Body Style:**

Plain

**Concentric Hole Depth:**

1.015 inches

**Concentric Hole Diameter:**

0.113 inches

**Overall Length:**

2.141 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal pipe

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

0.106 inches

**End Application:**

F52 aircraft

**Width Across Flats:**

0.625 inches

**First End Thread Length:**

0.391 inches

**Second End Thread Length:**

0.962 inches

**Wrenching Feature Style:**

Hexagon

**Distance From Bolt End To Hole Center:**

0.120 inches

**First Diameter From Wrenching Feature:**

0.374 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

1.562 inches

**First Radial Fluid Hole Diameter:**

0.052 inches

**Distance From First Radial Hole Center To End Of Bolt:**

1.179 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

1.953 inches

**Wrenching Feature Height:**

0.172 inches

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.375 inches

**Second End Thread Size:**

0.125 inches

**Second End Thread Series Designator:**

Npt

**Special Features:**

Wrenching flat 0.208 in.Dia.Parallel to 0.052 dia.Hole within

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000, cond c4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0

**Mil-std (military Standard):**

Mil-s-5000 spec.