NSN 4730-00-559-1604



Fluid Passage Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4730-00-559-1604 **Body Style:** Plain **Concentric Hole Depth:** 1.015 inches **Concentric Hole Diameter:** 0.113 inches **Overall Length:** 2.141 inches **First End Connection Type:** Threaded external tube First End Style Designator: Plain First End Thread Class: **First End Thread Direction:** Right-hand **Second End Connection Type:** Threaded internal pipe **Second End Thread Direction:** Right-hand **Cotter Pin Hole Diameter:** 0.106 inches **End Application:** F52 aircraft Width Across Flats: 0.625 inches First End Thread Length: 0.391 inches Second End Thread Length: 0.962 inches **Wrenching Feature Style:** Hexagon **Distance From Bolt End To Hole Center:** 0.120 inches First Diameter From Wrenching Feature: 0.374 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 1.562 inches First Radial Fluid Hole Diameter: 0.052 inches

Distance From First Radial Hole Center To End Of Bolt:

1.179 inches

NSN 4730-00-559-1604

Fluid Passage Bolt - Page 2 of 2



| Length From Bearing Surface Of Wrenching Feature To Bolt End: |
|---|
| 1.953 inches |
| Wrenching Feature Height: |
| 0.172 inches |
| First End Thread Series Designator: |
| Unf |
| First End Thread Size: |
| 0.375 inches |
| Second End Thread Size: |
| 0.125 inches |
| Second End Thread Series Designator: |
| Npt |
| Special Features: |
| Wrenching flat 0.208 in.Dia.Parallel to 0.052 dia.Hole within |
| Material: |
| Steel comp 4340 |
| Material Specification: |
| Mil-s-5000, cond c4 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A121a0 |
| Mil-std (military Standard): |
| Mil-s-5000 spec. |