

View Online at https://aerobasegroup.com/nsn/4730-00-580-8543

| Thread Class |
|---|
| Thread Class: |
| 3a Thread Direction: |
| |
| Right-hand |
| Overall Length: |
| 2.375 inches |
| Overall Width: |
| 1.188 inches |
| Thickness: |
| 1.000 inches |
| Thread Size: |
| 7/16 -20 |
| Thread Provision: |
| Threaded |
| Connection Style: |
| Flared |
| Bolt Hole Diameter: |
| 0.500 inches |
| Seat Angle In Deg: |
| 37.0 |
| Screw Thread Series Designator: |
| Unf |
| Seat: |
| Included |
| Deg Between Outlets: |
| 90.0 |
| Fluid Connection Quantity: |
| 3 |
| Fluid Conveyance Type And Size For Which Designed: |
| 1/4 in. Od tube |
| Bolt Hole Flats Serrations: |
| Not provided |
| Bolt Hole Fluid Passage: |
| Provided |
| Second Deg Between Outlets: |
| 90.0 |
| Material: |
| Aluminum alloy, qq-a-225/4, alloy 2014, t6 or aluminum alloy, qq-a-367, comp 2014, t6 |
| Material: |
| Aluminum alloy 2014 or aluminum alloy 2014 |
| Surface Treatment: |
| Anodize |

Fluid Pressure Line Multiple Connector - Page 2 of 2



Style Designator:

3 fluid connections

Surface Treatment:

Anodized, mil-a-8625, type 2, class 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T385-g