NSN 4730-00-602-2449

Pipe To Tube Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-602-2449

| view Online at https://aerobasegroup.com/nsn/4730-00-602-2449 |
|---|
| Pipe Size Accommodated: |
| 1.250 inches 2nd end |
| Thread Class: |
| 2a 1st end |
| Maximum Operating Temp: |
| 121.0 degrees celsius single response |
| Connection Style: |
| Plain (pipe) 2nd end |
| Leg Length: |
| 2.380 inches 2nd end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.625 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Flow Angle: |
| 90.0 degrees |
| Outside Diameter Tube Accommodated: |
| 1.250 inches 1st end |
| Material: |
| Steel |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator: |
| Un 1st end |
| Furnished Items And Quantity: |
| 1 ferrule sleeve and 1 short coupling nut |
| Specification Data: |
| 96906-ms51815 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4730-00-602-2449

Pipe To Tube Elbow - Page 2 of 2



| _ | | | | | | | | | | |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | • | iza | 31 | ^ | n | |
| | | | | | | | | | | |

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.