

View Online at <https://aerobasegroup.com/nsn/4730-00-613-5293>

Body Style:

Body wrenching

Concentric Hole Diameter:

0.172 inches

Overall Length:

2.966 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

Second End Thread Class:

3a

Second End Thread Direction:

Right-hand

Width Across Flats:

Between 0.684 inches and 0.691 inches

First End Thread Length:

Between 0.850 inches and 0.895 inches

Second End Thread Length:

0.550 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.499 inches

Second Diameter From Wrenching Feature:

0.433 inches

Third Diameter From Wrenching Feature:

0.499 inches

Fourth Diameter From Wrenching Feature:

0.364 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.354 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.666 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

1.027 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

1.199 inches

First Radial Fluid Hole Diameter:

0.189 inches

Distance From First Radial Hole Center To End Of Bolt:

1.532 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

2.072 inches

Wrenching Feature Height:

0.344 inches

First End Thready Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unf

First End Seat Angle:

37.0 degrees

First End Thread Size:

0.438 inches

Second End Seat Angle:

37.0 degrees

Second End Thready Qty Per Inch (tpi):

20

Second End Thread Size:

0.438 inches

Second End Thread Series Designator:

Unf

Material:

Aluminum alloy

Material Specification:

Qq-a-268, t4 federal specification single material response

Surface Treatment:

Anodize

Specification Data:

96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-f-5509 spec.