NSN 4730-00-618-4225

Fluid Pressure Line Multiple Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-618-4225 **Thread Class:** За **Thread Direction:** Right-hand **Overall Length:** 1.697 inches **Overall Width:** 1.000 inches Thickness: 0.968 inches **Thread Size:** 9/16 in.-18 **Thread Provision:** Threaded **End Application:** Aircraft application **Connection Style:** Flared **Bolt Hole Diameter:** Between 0.547 inches and 0.564 inches Seat Angle In Deg: 37.0 **Screw Thread Series Designator:** Unf Seat: Included **Deg Between Outlets:** 45.0 Fluid Connection Quantity: Fluid Conveyance Type And Size For Which Designed: 3/8 in. Od tube **Bolt Hole Flats Serrations:** Not provided **Bolt Hole Fluid Passage:** Provided

Special Features:
3000.0 psi maximum pressure

Material:
Aluminum alloy, qq-a-225/4, alloy 2014, t6

Material:
Aluminum alloy 2014

NSN 4730-00-618-4225

Fluid Pressure Line Multiple Connector - Page 2 of 2



| Surface Treatments |
|---|
| Surface Treatment: |
| Anodize |
| Style Designator: |
| 1 fluid connection |
| Surface Treatment: |
| Anodized, mil-a-8625, type 2, class 2 |
| Specification Data: |
| 80205-nas554 professional/industrial association standard and 81343-as4875/1 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T385-g |
| Mil-std (military Standard): |
| Mil-f-5509 spec. |