

View Online at https://aerobasegroup.com/nsn/4730-00-620-6937

| Tŀ | nread Class: |
|-----|--|
| 3a | all ends |
| 0 | verall Length: |
| 3. | 131 inches |
| Qı | uick Disconnect Method: |
| Qı | uick lead thread all ends |
| Qı | uick Disconnect Size: |
| 1.8 | 828 inches all ends |
| Co | onnection Style: |
| Fla | ared all ends |
| Le | eg Length: |
| 1.(| 060 inches |
| Co | onnection Type: |
| Th | nreaded external tube first fluid end connection |
| Fe | eatures Provided: |
| Se | elf-sealing |
| Tŀ | nready Qty Per Inch (tpi): |
| 12 | 2 all ends |
| Tŀ | nread Size: |
| 1.2 | 250 inches all ends |
| Se | eat Angle: |
| 37 | 7.0 degrees |
| 0 | utside Diameter Tube Accommodated: |
| 1.(| 000 inches all ends |
| Sp | pecial Features: |
| 21 | lockwire holes |
| Ma | aterial: |
| Al | uminum alloy body |
| Sι | urface Treatment: |
| Ar | nodize body |
| St | yle Designator: |
| Ma | ale coupling half |
| Tŀ | nread Series Designator: |
| Ur | njf all ends |
| Sł | nelf Life: |
| N/ | a |
| Ur | nit Of Measure: |
| | |
| De | emilitarization: |
| No | |
| Fi | ig: |
| | 531t0 |