

View Online at <https://aerobasegroup.com/nsn/4730-00-627-1366>

Body Style:

Body wrenching

Concentric Hole Diameter:

0.422 inches

Overall Length:

3.459 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flareless

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flareless

Second End Thread Class:

3a

Second End Thread Direction:

Right-hand

Width Across Flats:

Between 0.996 inches and 1.003 inches

First End Thread Length:

Between 1.051 inches and 1.096 inches

Second End Thread Length:

0.562 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.811 inches

Second Diameter From Wrenching Feature:

0.740 inches

Third Diameter From Wrenching Feature:

0.811 inches

Fourth Diameter From Wrenching Feature:

0.660 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.377 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.826 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

1.209 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

1.386 inches

First Radial Fluid Hole Diameter:

0.300 inches

Distance From First Radial Hole Center To End Of Bolt:

1.826 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

2.460 inches

Wrenching Feature Height:

0.437 inches

First End Thready Qty Per Inch (tpi):

16

First End Thread Series Designator:

Unjf

First End Seat Angle:

12.0 degrees

First End Thread Size:

0.750 inches

Second End Seat Angle:

12.0 degrees

Second End Thready Qty Per Inch (tpi):

16

Second End Thread Size:

0.750 inches

Second End Thread Series Designator:

Unjf

Material:

Aluminum alloy

Material Specification:

Qq-a-268, t4 federal specification single material response

Surface Treatment:

Anodize

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0