NSN 4730-00-630-7103 Fluid Pressure Line Multiple Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-00-630-7103 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| Any acceptable |
| Overall Width: |
| Between 0.675 inches and 0.678 inches |
| Thickness: |
| 0.500 inches |
| Thread Size: |
| 0.438-20 |
| Thread Provision: |
| Threaded |
| Connection Style: |
| Flareless |
| Bolt Hole Diameter: |
| 0.375 inches |
| Seat Angle In Deg: |
| 12.0 |
| Screw Thread Series Designator: |
| Jnf |
| Seat: |
| ncluded |
| Fluid Connection Quantity: |
| 1 |
| Fluid Conveyance Type And Size For Which Designed: |
| 0.250 in.Od tube |
| Bolt Hole Flats Serrations: |
| Not provided |
| Bolt Hole Fluid Passage: |
| Provided |
| Material: |
| Steel, federal standard 66, comp 431 |
| Surface Treatment: |
| Passivate |
| Style Designator: |
| 1 fluid connection |
| Surface Treatment: |
| Passivated |
| Shalf Life: |

N/a

NSN 4730-00-630-7103

Fluid Pressure Line Multiple Connector - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

T385-g