

View Online at <https://aerobasegroup.com/nsn/4730-00-633-5536>

Body Style:

Plain

Concentric Hole Depth:

1.156 inches

Concentric Hole Diameter:

0.172 inches

Overall Length:

1.375 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

0.688 inches

First End Thread Length:

0.437 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.435 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.750 inches

First Radial Fluid Hole Diameter:

0.188 inches

Distance From First Radial Hole Center To End Of Bolt:

0.781 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.188 inches

Wrenching Feature Height:

0.188 inches

First End Thread Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unf

First End Seat Angle:

45.0 degrees

First End Thread Size:

0.437 inches

Special Features:

Two 0.946 in. Diameter lockwire hole drilled in head

Material:

Aluminum alloy

Material Specification:

Qq-a-200/3 federal specification single material response or qq-a-225/5 federal specification 2nd material response or qq-a-250/4 federal specification 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Departure From Cited Designator:

This bolt is identical to an775-4 bolt with the exception of two drilled holes in head for lockwire

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-a-8625 spec.