

View Online at <https://aerobasegroup.com/nsn/4730-00-633-5536>

**Body Style:**

Plain

**Concentric Hole Depth:**

1.156 inches

**Concentric Hole Diameter:**

0.172 inches

**Overall Length:**

1.375 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Flared

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Width Across Flats:**

0.688 inches

**First End Thread Length:**

0.437 inches

**Wrenching Feature Style:**

Hexagon

**First Diameter From Wrenching Feature:**

0.435 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.750 inches

**First Radial Fluid Hole Diameter:**

0.188 inches

**Distance From First Radial Hole Center To End Of Bolt:**

0.781 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

1.188 inches

**Wrenching Feature Height:**

0.188 inches

**First End Thread Qty Per Inch (tpi):**

20

**First End Thread Series Designator:**

Unf

**First End Seat Angle:**

45.0 degrees

**First End Thread Size:**

0.437 inches

**Special Features:**

Two 0.946 in. Diameter lockwire hole drilled in head

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-200/3 federal specification single material response or qq-a-225/5 federal specification 2nd material response or qq-a-250/4 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Departure From Cited Designator:**

This bolt is identical to an775-4 bolt with the exception of two drilled holes in head for lockwire

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0

**Mil-std (military Standard):**

Mil-a-8625 spec.