

View Online at <https://aerobasegroup.com/nsn/4730-00-640-6823>

**Bolt Circle Diameter:**

Between 4.875 inches and 5.500 inches

**Flange Diameter:**

Between 6.585 inches and 6.625 inches

**Thickness:**

Between 0.500 inches and 0.609 inches

**Socket Diameter:**

Between 3.484 inches and 3.507 inches

**Bore Diameter:**

3.500 inches

**Pipe Size For Which Designed:**

3.000 inches

**Bolt Hole Quantity:**

8

**Bolt Hole Diameter:**

0.562 inches

**Neck Height:**

0.875 inches

**Flange Section Style:**

Plain face, socket brazing neck

**Face Seating Surface Condition:**

Machined

**Maximum Operating Pressure And Media For Which Designed:**

150.0 pounds per square inch gas and 150.0 pounds per square inch oil and 150.0 pounds per square inch steam and 150.0 pounds per square inch water

**Maximum Operating Temperature And Media For Which Designed:**

425.0 degrees fahrenheit gas and 425.0 degrees fahrenheit oil and 425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water

**Material:**

Copper alloy or copper

**Material Specification:**

Mil-f-20042 military specification single material response

**Style Designator:**

Round, one bolt hole circle

**Specification Or Standard:**

Pr type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23300

**Mil-std (military Standard):**

Mil-f-20042 spec.