

View Online at <https://aerobasegroup.com/nsn/4730-00-640-6823>

Bolt Circle Diameter:

Between 4.875 inches and 5.500 inches

Flange Diameter:

Between 6.585 inches and 6.625 inches

Thickness:

Between 0.500 inches and 0.609 inches

Socket Diameter:

Between 3.484 inches and 3.507 inches

Bore Diameter:

3.500 inches

Pipe Size For Which Designed:

3.000 inches

Bolt Hole Quantity:

8

Bolt Hole Diameter:

0.562 inches

Neck Height:

0.875 inches

Flange Section Style:

Plain face, socket brazing neck

Face Seating Surface Condition:

Machined

Maximum Operating Pressure And Media For Which Designed:

150.0 pounds per square inch gas and 150.0 pounds per square inch oil and 150.0 pounds per square inch steam and 150.0 pounds per square inch water

Maximum Operating Temperature And Media For Which Designed:

425.0 degrees fahrenheit gas and 425.0 degrees fahrenheit oil and 425.0 degrees fahrenheit steam and 425.0 degrees fahrenheit water

Material:

Copper alloy or copper

Material Specification:

Mil-f-20042 military specification single material response

Style Designator:

Round, one bolt hole circle

Specification Or Standard:

Pr type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23300

Mil-std (military Standard):

Mil-f-20042 spec.