NSN 4730-00-684-0506

Fluid Passage Bolt - Page 1 of 3

0.666 inches



View Online at https://aerobasegroup.com/nsn/4730-00-684-0506

Body Style:
Body wrenching
Concentric Hole Diameter:
0.203 inches
Overall Length:
3.028 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Flared
First End Thread Class:
За
First End Thread Direction:
Right-hand
Second End Connection Type:
Threaded external tube
Second End Style Designator:
Flared
Second End Thread Class:
За
Second End Thread Direction:
Right-hand
Width Across Flats:
Between 0.746 inches and 0.753 inches
First End Thread Length:
0.688 inches
Second End Thread Length:
0.550 inches
Wrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature:
0.499 inches
Second Diameter From Wrenching Feature:
0.433 inches
Third Diameter From Wrenching Feature:
0.499 inches
Fourth Diameter From Wrenching Feature:
0.364 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0.354 inches
Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:
0 666 inches

NSN 4730-00-684-0506

Fluid Passage Bolt - Page 2 of 3



Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:
1.027 inches
Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:
1.200 inches
First Radial Fluid Hole Diameter:
0.189 inches
Distance From First Radial Hole Center To End Of Bolt:
1.532 inches
Length From Bearing Surface Of Wrenching Feature To Bolt End:
2.072 inches
Wrenching Feature Height:
0.406 inches
First End Thready Qty Per Inch (tpi):
20
First End Thread Series Designator:
Unf
First End Seat Angle:
37.0 degrees
First End Thread Size:
0.438 inches
Second End Seat Angle:
37.0 degrees
Second End Thready Qty Per Inch (tpi):
20
20
20 Second End Thread Size:
20 Second End Thread Size: 0.500 inches
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard Shelf Life:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:
20 Second End Thread Size: 0.500 inches Second End Thread Series Designator: Unf Material: Aluminum alloy 2024 Material Specification: Qq-a-268 federal specification single material response Surface Treatment: Anodize Specification Data: 96906-ms21950 government standard and 81343-as4875/1 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

NSN 4730-00-684-0506

Fluid Passage Bolt - Page 3 of 3

Mil-std (military Standard):

Mil-f-5509 spec.

