

View Online at <https://aerobasegroup.com/nsn/4730-00-684-7155>

Body Style:

Body wrenching

Concentric Hole Depth:

1.812 inches

Concentric Hole Diameter:

0.203 inches

Overall Length:

2.431 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

Second End Thread Class:

3a

Second End Thread Direction:

Right-hand

Width Across Flats:

0.875 inches

First End Thread Length:

0.239 inches

Second End Thread Length:

0.556 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.425 inches

Second Diameter From Wrenching Feature:

0.499 inches

Third Diameter From Wrenching Feature:

0.433 inches

Fourth Diameter From Wrenching Feature:

0.499 inches

Fifth Diameter From Wrenching Feature:

0.363 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.052 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.354 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

0.666 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

1.027 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fifth Diameter:

1.199 inches

First Radial Fluid Hole Diameter:

0.189 inches

Distance From First Radial Hole Center To End Of Bolt:

0.898 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.438 inches

Wrenching Feature Height:

0.437 inches

First End Thready Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unjf

First End Thread Size:

0.437 inches

Second End Seat Angle:

37.0 degrees

Second End Thready Qty Per Inch (tpi):

18

Second End Thread Size:

0.562 inches

Second End Thread Series Designator:

Unf

Material:

Aluminum

Surface Treatment:

Anodize

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0