## NSN 4730-00-684-7232

Fluid Pressure Line Multiple Connector - Page 1 of 2



<u> </u>
View Online at https://aerobasegroup.com/nsn/4730-00-684-7232
Thread Class:
3a
Thread Direction:
Right-hand
Overall Length:
Between 1.703 inches and 1.875 inches
Overall Width:
1.000 inches
Thickness:
0.875 inches
Thread Size:
9/16 in18
Thread Provision:
Threaded
Connection Style:
Flared
Bolt Hole Diameter:
Between 0.563 inches and 0.565 inches
Seat Angle In Deg:
37.0
Screw Thread Series Designator:
Unf
Seat:
Included
Deg Between Outlets:
75.0
Fluid Connection Quantity:
1
Fluid Conveyance Type And Size For Which Designed:
3/8 in. Od tube
Bolt Hole Flats Serrations:
Provided
Bolt Hole Fluid Passage:
Provided
Material:
Steel, federal standard 66, comp 304
Material:
Steel comp 304
Surface Treatment:
Passivate

Style Designator:

1 fluid connection

## NSN 4730-00-684-7232

Mil-f-5509 spec.

Fluid Pressure Line Multiple Connector - Page 2 of 2



Surface Treatment:
Passivated, qq-p-35
Specification Data:
81343-as4875/1 professional/industrial association standard and 88044-an777 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T385-g
Mil-std (military Standard):