

View Online at <https://aerobasegroup.com/nsn/4730-00-689-1231>

**Thread Class:**

2a center bulkhead

**Maximum Operating Temp:**

250.0 degrees fahrenheit 1st response

**Connection Style:**

Flareless (tube) all ends

**Connection Type:**

Threaded external tube all ends

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.562 inches all ends

**Seat Angle:**

12.0 degrees all ends

**Outside Diameter Tube Accommodated:**

0.375 inches all ends

**Nominallength:**

1.980 inches

**Material:**

Steel comp 12L14 or steel comp 1010

**Material Specification:**

66, carbon steel, 0.20 percent maximum federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 1st response

**Surface Treatment Specification:**

J514 assn standard single treatment response and qq-p-416, type 2, cl 3 federal specification 1st treatment response and mil-c-81562, type 2, cl 3 military specification 2nd treatment response

**Style Designator:**

Flaremess w/ bulkhead threads

**Thread Series Designator:**

Unf center bulkhead

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve and 1 bulkhead nut

**Specification Data:**

96906-ms51812 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

20a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-c-81562 spec.