

View Online at <https://aerobasegroup.com/nsn/4730-00-689-1231>

Thread Class:

2a center bulkhead

Maximum Operating Temp:

250.0 degrees fahrenheit 1st response

Connection Style:

Flareless (tube) all ends

Connection Type:

Threaded external tube all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

0.375 inches all ends

Nominallength:

1.980 inches

Material:

Steel comp 12L14 or steel comp 1010

Material Specification:

66, carbon steel, 0.20 percent maximum federal standard single material response

Media For Which Designed:

Hydraulic fluid 1st response

Surface Treatment Specification:

J514 assn standard single treatment response and qq-p-416, type 2, cl 3 federal specification 1st treatment response and mil-c-81562, type 2, cl 3 military specification 2nd treatment response

Style Designator:

Flaremess w/ bulkhead threads

Thread Series Designator:

Unf center bulkhead

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 bulkhead nut

Specification Data:

96906-ms51812 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

20a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-c-81562 spec.