

View Online at <https://aerobasegroup.com/nsn/4730-00-689-5994>

**Thread Class:**

2a 1st end

**Maximum Operating Temp:**

256.0 degrees fahrenheit 2nd response

**Connection Style:**

Plain (pipe) 2nd end

**Leg Length:**

0.984 inches 1st end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

45.0 degrees

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Steel comp 12114 sleeve or steel comp 1212 sleeve

**Material Specification:**

66, carbon steel, 0.20 percent maximum federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-c-16232, type m, class 1 military specification single treatment response

**Thread Series Designator:**

Unf 1st end

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve

**Specification Data:**

96906-ms51817 government standard

**Specification Or Standard:**

21 figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-c-16232 spec.