## NSN 4730-00-700-5072

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-700-5072 **Body Style:** Shoulder **Concentric Hole Depth:** 2.438 inches **Concentric Hole Diameter:** 0.375 inches **Overall Length:** 5.250 inches **First End Connection Type:** Threaded external tube First End Style Designator: Plain First End Thread Class: **First End Thread Direction:** Right-hand **Cotter Pin Hole Diameter:** 0.188 inches Width Across Flats: 1.625 inches First End Thread Length: 0.656 inches **Wrenching Feature Style:** Hexagon **Distance From Bolt End To Hole Center:** 0.188 inches First Diameter From Wrenching Feature: Between 1.2488 inches and 1.250 inches **Second Diameter From Wrenching Feature:** 0.875 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 4.219 inches First Radial Fluid Hole Diameter: 0.250 inches **Distance From First Radial Hole Center To End Of Bolt:** 

**Length From Bearing Surface Of Wrenching Feature To Bolt End:** 4.875 inches

Wrenching Feature Height:

0.375 inches

2.812 inches

## NSN 4730-00-700-5072

Fluid Passage Bolt - Page 2 of 2

A121a0



Hardness Rating:
Between 85.0 rockwell superficial 15-n and 90.0 rockwell superficial 15-n
First End Thready Qty Per Inch (tpi):
14
First End Thread Series Designator:
Unf
First End Thread Size:
1.000 inches
Material:
Steel
Material Specification:
$\label{eq:q-s-633} Qq\text{-s-633}, fs 1010 \ to \ fs 1020 \ or \ fs 1117 \ to \ fs 1120 \ federal \ specification \ single \ material \ response \ for \ response \ re$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: