NSN 4730-00-720-0692

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-720-0692

Body Style:
Plain
Concentric Hole Depth:
0.937 inches
Concentric Hole Diameter:
0.172 inches
Overall Length:
1.375 inches
First End Connection Type:
Threaded external tube
First End Style Designator:
Inverted flare
First End Thread Class:
3a
Sa First End Thread Direction:
Right-hand
Width Across Flats:
0.688 inches
First End Thread Length:
0.406 inches
Wrenching Feature Style:
Hexagon
First Diameter From Wrenching Feature: 0.435 inches
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:
0.781 inches First Radial Fluid Hole Diameter:
0.172 inches
0.172 inches Distance From First Radial Hole Center To End Of Bolt:
0.796 inches Length From Bearing Surface Of Wrenching Feature To Bolt End:
Length From Bearing Surface Of Wrenching Feature To Bolt End: 1.187 inches
Wrenching Feature Height: 0.188 inches
First End Thready Qty Per Inch (tpi):
20 First End Throad Series Designator:
First End Thread Series Designator:
Unf First End Seat Angle:
First End Seat Angle:
45.0 degrees First End Thread Size:
0.437 inches

NSN 4730-00-720-0692

Fluid Passage Bolt - Page 2 of 2



Special Features:
Drilled for lockwire
Material:
Aluminum
Surface Treatment:
Anodize
Specification Data:
81343-as4875 professional/industrial association standard and 80205-nas551 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A121a0
Mil-std (military Standard):
Mil-f-5509 spec.