## NSN 4730-00-722-5467

Tube Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-722-5467

| Maximum Operating Temp:  150.0 degrees fahrenheit single response  Connection Style:  Plain (tube) 1st end  Maximum Operating Pressure:  200.0 pounds per square inch single response  Outside Diameter Tube Accommodated:  1.900 inches 1st end  Nominallength:  1.250 inches  Special Features:  For salt water use  Material:  Copper alloy  Material Specification:  Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics:  As differentiated by item name and od tube size  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A080b0  Mil-std (military Standard): |   |
|---|---|
| Connection Style: Plain (tube) 1st end Maximum Operating Pressure: 200.0 pounds per square inch single response Outside Diameter Tube Accommodated: 1.900 inches 1st end Nominallength: 1.250 inches Special Features: For salt water use Material: Copper alloy Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):  | Maximum Operating Temp:   |
| Plain (tube) 1st end  Maximum Operating Pressure: 200.0 pounds per square inch single response  Outside Diameter Tube Accommodated: 1.900 inches 1st end  Nominallength: 1.250 inches  Special Features: For salt water use  Material: Copper alloy  Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):   | 150.0 degrees fahrenheit single response                                      |
| Maximum Operating Pressure: 200.0 pounds per square inch single response Outside Diameter Tube Accommodated: 1.900 inches 1st end Nominallength: 1.250 inches Special Features: For salt water use Material: Copper alloy Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | Connection Style:   |
| 200.0 pounds per square inch single response  Outside Diameter Tube Accommodated: 1.900 inches 1st end  Nominallength: 1.250 inches  Special Features: For salt water use  Material: Copper alloy  Material Specification:  Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):   | Plain (tube) 1st end  |
| Outside Diameter Tube Accommodated:  1.900 inches 1st end  Nominallength:  1.250 inches  Special Features: For salt water use  Material:  Copper alloy  Material Specification:  Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life:  N/a  Unit Of Measure:  Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):   | Maximum Operating Pressure:   |
| 1.900 inches 1st end  Nominallength: 1.250 inches  Special Features: For salt water use  Material: Copper alloy  Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):  | 200.0 pounds per square inch single response                                  |
| Nominallength:  1.250 inches  Special Features: For salt water use  Material: Copper alloy  Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):  | Outside Diameter Tube Accommodated:   |
| 1.250 inches  Special Features: For salt water use  Material: Copper alloy  Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig: A080b0  Mil-std (military Standard):  | 1.900 inches 1st end  |
| Special Features: For salt water use  Material: Copper alloy Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):  | Nominallength:  |
| Material: Copper alloy Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):  | 1.250 inches  |
| Material: Copper alloy Material Specification: Mil-t-16420 90-1 (uns c70600) military specification single material response Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):  | Special Features:   |
| Copper alloy  Material Specification:  Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics:  As differentiated by item name and od tube size  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A080b0  Mil-std (military Standard):  | For salt water use  |
| Material Specification:  Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics:  As differentiated by item name and od tube size  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A080b0  Mil-std (military Standard):   | Material:   |
| Mil-t-16420 90-1 (uns c70600) military specification single material response  Reference Number Differentiating Characteristics: As differentiated by item name and od tube size  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | Copper alloy  |
| Reference Number Differentiating Characteristics: As differentiated by item name and od tube size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | Material Specification:   |
| As differentiated by item name and od tube size  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):  | Mil-t-16420 90-1 (uns c70600) military specification single material response |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | Reference Number Differentiating Characteristics:                             |
| N/a Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | As differentiated by item name and od tube size                               |
| Unit Of Measure: Demilitarization: No Fiig: A080b0 Mil-std (military Standard):   | Shelf Life:   |
| Demilitarization:  No Fiig: A080b0 Mil-std (military Standard):   | N/a   |
| No Fiig: A080b0 Mil-std (military Standard):  | Unit Of Measure:  |
| No Fiig: A080b0 Mil-std (military Standard):  |   |
| Fiig:<br>A080b0<br>Mil-std (military Standard):   | Demilitarization:   |
| A080b0  Mil-std (military Standard):  | No  |
| Mil-std (military Standard):  | Fiig:   |
|   | A080b0  |
| MW - 40400  | Mil-std (military Standard):  |
| Mil-t-16420 spec.   | Mil-t-16420 spec.   |
|   |   |
| Mil-t-16420 spec.   | A080b0  Mil-std (military Standard):  |