

View Online at https://aerobasegroup.com/nsn/4730-00-727-5844

| Thread Class: |
|--|
| 3a 1st end |
| |
| Bolt Hole Quantity: |
| 4 2nd end |
| Connection Style: |
| Flared (tube) 1st end |
| Width: |
| 2.190 inches 2nd end |
| Length: |
| 2.190 inches 2nd end |
| Flange Shape: |
| Rectangular with holes 2nd end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Thread Size: |
| 1.312 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Union Joint Location: |
| First end |
| Thickness: |
| 0.380 inches 2nd end |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.656 inches 2nd end |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.656 inches 2nd end |
| Flange Face Design: |
| Plain 2nd end |
| Outside Diameter Tube Accommodated: |
| 1.500 inches 1st end |
| Nominallength: |
| 1.500 inches |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Anodize outside |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |

Flange To Tube Straight Adapter - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A080b0