

View Online at <https://aerobasegroup.com/nsn/4730-00-727-9784>

Thread Class:

2a all ends

Maximum Operating Temp:

121.0 degrees celsius single response

End Application:

Tank, combat 152-mm gun/launcher, m60a2

Connection Style:

Flareless (tube) 1st end

Leg Length:

0.891 inches 1st end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

12.0 degrees 1st end

Flow Angle:

90.0 degrees

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Steel comp 1213 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 12114

Material Specification:

66 federal standard single material response

Media For Which Designed:

Hydraulic fluid 1st response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-c-16232, type m, class 1 military specification single treatment response

Thread Series Designator:

Unf all ends

Specification Data:

96906-ms51839 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-c-16232 spec.